



LED PANEL

LED Lighting Solutions
Professional, Innovation, Customization



ABOUT US

Foshan Hortilite Optoelectronics Co., Ltd. is a joint venture of two public listed lighting manufacturers, FSL (stock code: 000541) and NATIONSTAR (stock code: 002449), a LED innovative lighting solution supplier integrating R&D, manufacturing, sales and customer service.

The purpose to establish this joint company is for a better future growth and development of our lighting business. We are based on the same team of the LED Lighting Division of NATIONSTAR, which has more than 15 years experience in OEM and ODM service for customers in Germany, Italy, Spain, Russia, US, Canada etc., mainly focusing on LED panel, LED batten, LED flexible strips and LED horticulture lighting.

With excellent R&D team and supreme manufacturing standard, we are offering precise and top performance LED products with industry leading technology.

Our goal is not only to meet your requirements, but exceed your expectations.



Founded in 1958, FSL is one of the most competitive lighting brands across China, providing clients with full-range professional lighting solutions. It owns five production bases in Guangdong Province, Henan Province, Jiangsu Province, etc. A complete supply chain system from R&D, manufacturing, sales, services, enabling FSL to produce on a mass scale covering residential lighting, commercial lighting and outdoor lighting.



NATIONSTAR is a national level high-tech enterprise with professional capability in manufacturing LED components (White, RGB and non-visual LED). Founded in 1969, Nationstar ranks the 8th. globally in the list of revenue and market shares for LED packages in 2018 (IHS Markit).



Background Support


Supported by the mature supply chain system, large-scale production capacity of FSL and leading LED technical advantages of NATIONSTAR.



Manufacturing Experience

One of the earliest LED lighting products manufacturer in China.

LED flexible strips since 2006, LED panel since 2010, LED batten since 2016, LED horticulture lighting since 2019.





▲ Integrating Sphere

R & D Strength

More than 30 excellent and professional engineers in electronics, optics, structure, industrial design and other related fields. Professional laboratory (UL&CNAS) are equipped.



▲ Reliability



▲ Lighting Distribution

Precise and Flexible Manufacturing Mode

Equipped with SMT lines, automatic soldering machines, automatic screw machines, automatic silicone extrusion equipment, automatic aging equipment, etc. to guarantee excellent performance of each product. Offer standard products as well as customized service.



▲ Rolling and Cutting



▲ Bending



▲ Powder Spraying



▲ LSP Silk Screen Printing



▲ Assembling



▲ Semi-automatic Assembling



▲ Automatic Screw



▲ Aging

LED PANEL | Indoor lighting

Suspended



Linear Panel PRO




Rectangle Panel



Round Panel PRO




Round Panel ECO



Wifi/Bluetooth
Smart Panel



Square Panel PRO




Recessed ceiling
panel

Recessed



Square Panel PRO



Recessed ceiling
panel




Round Panel in
small size

Surface mounted



Square Panel PRO



Recessed ceiling
panel




Linear Panel



Square Panel in
small size

LED PANEL | Track lighting

Track mounted



Track Panel H



Track Panel G



Track Panel I




Track Panel K




Track Panel L

LED PANEL | Higher protection

Recessed



Clean panel



PLS-J





Grille Panel Light




Suspended

Linear Panel PRO EU



110° Photometric



AC 220-240V	IP20	Ra 80/90	110°	DALI	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	------	------	-----	-------------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-30120	L200*W1200*H20	30	3600	120



*Lumen and Wattage: Type value with ±10% tolerance

- Construction**
- Frame | Aluminum
 - Back plate | Galvanized steel
 - LGP | PMMA
 - Diffuser | PS
- 3000K 4000K 6500K

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L



EU Rectangle Panel



3060H 110° Photometric

Construction

Frame | Al

Back plate | Galvanized Steel

Diffuser | PS

3000K 4000K 6500K



- AC 230V
- IP20
- Ra 80/90
- 110°
- PF > 0.9
- 3SDCM LED
- housing

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLD-3060H	L600*W300*H35	40	4400	110

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L

Round Panel PRO EU



3060H 110° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | PS



AC 220-240V	IP20	Ra 80/90	110°	DALI	0-10V	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	------	------	-------	-----	-------------	--------------



Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-R30P	Ø400mm *H25mm	30	3300	110
HLT-PLS-R40P	Ø600mm *H25mm	40	4400	
HLT-PLS-R60P	Ø780mm *H25mm	60	6600	

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L



EU *Round Panel ECO*



PLS-6060 110° Photometric



Construction

- Frame | Steel
- Back plate | Steel
- Diffuser | PS





AC 220-240V	IP20	Ra80	110°	PF > 0.9	5SDCM LED
----------------	------	------	------	----------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLD-R30	Ø400mm *H60mm	30	3000	100
HLT-PLD-R40	Ø600mm *H60mm	40	4000	
HLT-PLD-R60	Ø800mm *H60mm	60	6000	

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L

Wifi/Bluetooth Smart Panel **EU**



90° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | PS



Brightness dimmable:



CCT adjustable:





intelligent control module optional

AC 220-240V	IP20	Ra 80/90	110°	DALI	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	------	------	-----	-------------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-6060	L595*W595*H8.5	30	3750	125
HLT-PLS-6262	L620*W620*H8.5	30	3750	

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L



90° Photometric

Construction

Frame | Aluminum

Back plate | Galvanized steel

LGP | PMMA

Diffuser | Prism polystyrene

3000K 4000K 6500K



Prism diffuser

EU Square Panel PRO





AC 220-240V	IP20	Ra 80/90	90°	DALI	0-10V	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	-----	------	-------	-----	-------------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS2-6060/6262	6060/6262	30	4200	140

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L

Recessed ceiling panel **EU**



110° Photometric

- AC 220-240V
- IP20
- Ra80
- 110°
- PF > 0.9
- 5SDCM LED

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-15120	L150*W1200*H9.5	30	2700	90
HLT-PLS-20120	L200*W1200*H9.5	30	2700	90
HLT-PLS-30120	L300*W1200*H9.5	36	3420	95

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Suspension Kits	A01502	Type L



Construction
 Frame | Aluminum
 Back plate | Galvanized steel
 LGP | PMMA
 Diffuser | PS

3000K 4000K 6500K



Recessed

Square Panel PRO EU



90° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | Prism polystyrene



Prism diffuser

AC 220-240V	IP20	Ra 80/90	90°	DALI	0-10V	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	-----	------	-------	-----	----------	--------------



Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS2-6060/6262	6060/6262	30	4200	140

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit



EU Recessed ceiling panel



110° Photometric

Construction

Frame | Aluminum

Back plate | Galvanized steel

LGP | PMMA

Diffuser | PS

3000K 4000K 6500K



- AC 220-240V
- IP20
- Ra80
- 110°
- PF > 0.9
- 5SDCM LED

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-15120	L150*W1200*H9.5	30	2700	90
HLT-PLS-20120	L200*W1200*H9.5	30	2700	90
HLT-PLS-30120	L300*W1200*H9.5	36	3420	95

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit

Round Panel in small Size **EU**



90° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | Prism polystyrene



AC 220-240V	IP20	Ra80	 110°	PF > 0.9	5SDCM LED
----------------	------	------	----------	-------------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-D22J20	Ø 225mm	20w	2000lm	100lm/w



*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit



Surface mounted

Square Panel PRO EU



90° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | Prism polystyrene



Prism diffuser

AC 220-240V	IP20	Ra 80/90	90°	DALI	0-10V	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	-----	------	-------	-----	----------	--------------



Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS2-6060/6262	6060/6262	30	4200	140

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Frame ceiling kits	A01504	



EU Recessed ceiling panel



110° Photometric

Construction

Frame | Aluminum

Back plate | Galvanized steel

LGP | PMMA




Diffuser | PS

3000K 4000K 6500K



AC 220-240V	IP20	Ra80	 110°	PF > 0.9	5SDCM LED
----------------	------	------	--	----------	-----------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-15120	L150*W1200*H9.5	30	2700	90
HLT-PLS-20120	L200*W1200*H9.5	30	2700	90
HLT-PLS-30120	L300*W1200*H9.5	36	3420	95

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Frame ceiling kits	A01504	

Linear Panel **EU**



90° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | PS



AC 220-240V	IP20	Ra 80/90	110°	DALI	CCT	PF > 0.9	3SDCM LED
----------------	------	-------------	------	------	-----	-------------	--------------



Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-30120	L200*W1200*H20	30	3600	120

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Frame ceiling kits	A01504	



EU Square Panel in small size



90° Photometric



Construction

Frame | Aluminum

Back plate | Galvanized steel

LGP | PS

Diffuser | PS



Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLD-1212	L120*W120*H32	6	6000	100
HLT-PLD-2525	L225*W225*H32	18	1800	
HLT-PLD-3030	L300*W300*H32	24	2400	

*Lumen and Wattage: Type value with ±10% tolerance



Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Frame ceiling kits	A01504	




Track mounted



EU Track Panel H



3060H 110° Photometric



Construction

- Frame | Al
- Back plate | Galvanized steel
- Diffuser | PS




3000K 4000K 6500K

AC 230V	IP20	Ra 80/90	110°	PF > 0.9	3SDCM LED	housing
---------	------	----------	------	----------	-----------	---------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLD-3060H	L600*W300*H96	40	4400	110

*Lumen and Wattage: Type value with ±10% tolerance

Track Panel G EU



PLD-1358G Photometric

Construction

Housing | Al

Diffuser | PC Lens





3000K 4000K 6500K

AC 230V	IP20	Ra 80/90	DALI	PF > 0.9	3SDCM LED	housing
---------	------	----------	------	----------	-----------	---------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)	Beam Angle
HLT-PLD-1358G	L579*W127.5*H90.5	60	7800	130	Double asymmetric 25° (60°/90°/110°)

*Lumen and Wattage: Type value with ±10% tolerance

EU Track Panel I



PLD-1358I Photometric

3000K 4000K 6500K








- AC 230V
- IP20
- Ra 80/90
- DALI
- PF > 0.9
- 3SDCM LED
- housing

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)	Beam Angle
HLT-PLD-1358I	L579*W127.5*H71.5	40	5200	130	Double asymmetric 25° (60°/90°/110°)

*Lumen and Wattage: Type value with ±10% tolerance

Track Panel K **EU**



PLD-1358K Photometric




3000K 4000K 6500K

- AC 230V
- IP20
- Ra 80/90
- DALI
- PF > 0.9
- 3SDCM LED
- housing

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)	Beam Angle
HLT-PLD-1358K	L579*W127.5*H78	40	5200	130	60°/90°/110°

*Lumen and Wattage: Type value with ±10% tolerance

EU Track Panel L



90° Photometric

3000K 4000K 6500K



- AC 230V
- IP20
- Ra 80/90
- DALI
- PF > 0.9
- 3SDCM LED
- housing

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)	Beam Angle
PLS2-3011J20	L300*W110*H8.5	20	2200	110	110°



*Lumen and Wattage: Type value with ±10% tolerance



Recessed



EU *Clean Panel*



PLS-6060 110° Photometric

Construction

Frame | Aluminum

Back plate | Galvanized steel

LGP | PMMA




Diffuser | PS

3000K 4000K 6500K



AC 220-240V	IP20	Ra80	 110°	PF > 0.9	5SDCM LED
----------------	------	------	--	----------	-----------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-PLS-6060J36	L595*W595*H8.5	36	3960	110
HLT-PLS-6262J36	L620*W620*H8.5	36	3960	

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit


PLS-J EU



PLS-6060 110° Photometric

Construction

- Frame | Aluminum
- Back plate | Galvanized steel
- LGP | PMMA
- Diffuser | PS





AC 220-240V	IP20 ↑ IP54	Ra 80	110°	DALI	0-10V	CCT	PF > 0.9	5SDCM LED
----------------	-------------------	----------	------	------	-------	-----	-------------	--------------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)
HLT-PLS-6060J36	L595*W595*H8.5	36	3960
HLT-PLS-6262J36	L620*W620*H8.5	36	3960

*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit

Grille Panel Light EU



90° Photometric

Construction

Frame | PC
Back plate | Al



AC 220-240V	IP20	Ra80	110°	DALI	0-10V	PF > 0.9	5SDCM LED
----------------	------	------	------	------	-------	----------	-----------

Model No.	Size (mm)	Wattage (W)	Lumen (lm)	Efficacy (lm/W)
HLT-GSD-6060C28H	L597*W597*H35	28	3780	135




*Lumen and Wattage: Type value with ±10% tolerance

Accessories	Product Name	Code	Item
	DALI DT8 Flicker Free Driver	A01511	LF-GSD040YG
	Flicker Free Driver	A01501	MH-40C100M12
	Spring Brackets	A01503	Spring Bracket Kit

LED PANEL Installation Instruction




01 Built-in installation

Clear the keel and connect AC end with user AC end. Install the LED panel into the keel as illustrated.





02 Suspending Mounting

Make the hanging wires through the holes on fittings. Fix the anchoring onto the ceiling.






03 Surface Frame Mounting

Fix the bracket with screws into the ceiling, adjust the panel to be align with the hole, then slide right to lock.




04 Spring Buckle installation (plasterboard)

Clear the keel and connect AC end with user AC end. Install the LED panel into the keel as illustrated.





Foshan Hortilite Optoelectronics Co.,Ltd.

 TEL
+ 86-757-8228-2975

 MAIL
sales@hortilite.com

 WEB
www.hortilite.com

 ADD
19 Hengchang Road, Fuwan Industrial Park, Hecheng Street
Foshan, Guangdong, China